



ANTI SLIP / NON SLIP TAPES

**ANTI SLIP
NON SLIP TAPES**

ANTI SLIP NON SLIP TAPES

GENERAL DESCRIPTION

HS and SS series tapes are an excellent and economical solution improving the safety standards in slip hazard areas. They are available in 2 basic widths (5 cm and 10 cm). Installation is very simple – just follow the instructions below.



INSTALLATION

- 1 Make sure that the surface is clean and dry, free of oils, sand or dust.
- 2 Release a small piece of the release paper.
- 3 Apply the first part of the tape to the surface and continue removing the release foil gradually.
- 4 The full adhesive strength is achieved 48 hours after installation. Try to avoid heavy use of the tape during this time.
- 5 In view of the many types of the surfaces where the anti slip tapes can be applied – the final user should perform his own tests to ensure that the product is suitable for his application and that it meets his demands.

AVAILABILITY

HARD surface tapes (HS) – offer excellent anti-slip properties, however, because of the rough surface they are difficult in cleaning and cannot be washed with mops.

SOFT surface tapes (SS) – are a mop-friendly solution, they offer considerably lower anti-slippery properties, however, they are much easier in maintenance and cleaning.

PICTURE	PRODUCT CODE	SIZE	COLOUR TYPE	SURFACE
	HS-P	50 mm x 18 m 100 mm x 18 m	yellow-green (photoluminescent)	HARD
	HS-B	50 mm x 18 m 100 mm x 18 m	black	HARD
	HS-T	50 mm x 18 m 100 mm x 18 m	transparent	HARD
	HS-YB	50 mm x 18 m 100 mm x 18 m	yellow/black (diagonal stripes)	HARD
	SS-W	50 mm x 18 m 100 mm x 18 m	white	SOFT
	SS-B	50 mm x 18 m 100 mm x 18 m	black	SOFT
	SS-T	50 mm x 18 m 100 mm x 18 m	transparent	SOFT